



A brand of **TOTAL**

# ELF EVOLUTION 300 SAE 40



Monograde oil designed for petrol and diesel passenger car engines. Suitable for use under standard conditions.

## APPLICATIONS

### Gasoline and Diesel car engines

- These oils can be used with petrol or diesel engine technologies without particulate filters and engines built prior to 2004 and designed for use with mineral oils in these viscosities.

### In all conditions

- Suitable for all conditions (in town, on highways or motorways); Meets needs of motor manufacturers regarding extended oil change intervals

Refer to the maintenance book of your vehicle to know the recommendation of the

## PERFORMANCES

### International specifications

API SJ/CF

## CUSTOMER BENEFITS

- Protection and reliability
- Formulations are designed to resist to oxidation effects between oil changes
- Well-suited for old generation vehicles and engines
- Standard drain interval.

## CHARACTERISTICS

	Method	Units	SAE Grade 40
Density at 15°C	ASTM D1298	Kg/m <sup>3</sup>	
Viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	
Viscosity at 100°C	ASTM 445	mm <sup>2</sup> /s	
Viscosity index	ASTM D2270	-	
Pour point	ASTM D97	°C	
Flash point	ASTM D92	°C	
B.N.	ASTM D2896	mgKOH/g	

The typical characteristics mentioned represent mean values

**TOTAL LUBRIFIANTS – Immeuble Spazio**  
562, avenue du Parc de l'île  
92029 Nanterre cedex  
France

### ELF EVOLUTION 300 SAE 40

Last update of this datasheet: 10/2015



This lubricant used in accordance with our recommendations and for the application for which it is intended does not represent a special hazard. A safety data file conforming to the requirements of current EC legislation is available from your local trade consultant.