



A brand of **TOTAL**

ELF EVOLUTION 300 SAE 50



Monograde oil designed for petrol and diesel passenger car engines.
Suitable for use under standard conditions.

APPLICATIONS

Gasoline and Diesel car engines

• These oils can be used with petrol or diesel engine technologies without particulate filters and engines built prior to 2004 and designed for use with mineral oils in these viscosities.

In all conditions

• Suitable for all conditions (in town, on highways or motorways); Meets needs of motor manufacturers regarding extended oil change intervals

Refer to the maintenance book of your vehicle to know the recommendation of the

PERFORMANCES

International specifications

API SJ/CF

CUSTOMER BENEFITS

- Protection and reliability
- Formulations are designed to resist to oxidation effects between oil changes
- Well-suited for old generation vehicles and engines
- Standard drain interval.

CHARACTERISTICS

	Method	Units	SAE Grade 50
Density at 15°C	ASTM D1298	Kg/m ³	
Viscosity at 40°C	ASTM D445	mm ² /s	
Viscosity at 100°C	ASTM 445	mm ² /s	
Viscosity index	ASTM D2270	-	
Pour point	ASTM D97	°C	
Flash point	ASTM D92	°C	
B.N.	ASTM D2896	mgKOH/g	

The typical characteristics mentioned represent mean values

TOTAL LUBRIFIANTS – Immeuble Spazio
562, avenue du Parc de l'île
92029 Nanterre cedex
France

ELF EVOLUTION 300 SAE 50

Last update of this datasheet: 10/2015



This lubricant used in accordance with our recommendations and for the application for which it is intended does not represent a special hazard.
A safety data file conforming to the requirements of current EC legislation is available from your local trade consultant.