



A brand of **TOTAL**

# ELF EVOLUTION 500 FT 10W-40



*Premium multi-grade motor oil using ELF mineral technology, intended for lubricating gasoline passenger car engines*

## APPLICATIONS

### Most recent technology engines

- Premium multi-grade motor oil for all engines, recommended for all high performance gasoline engine cars equipped with direct or indirect injection, multi valve and turbo-charge technologies

### In all conditions

- Suitable for all conditions (in town, on highways or motorways); Meets needs of motor manufacturers regarding extended oil change intervals

Refer to the maintenance book of your vehicle to know the recommendation of the

## PERFORMANCES

### International specifications

API SN

## CUSTOMER BENEFITS

### Excellent engine protection

- Improved engine cleanliness
- Very high anti-wear and anti-corrosion properties that maintain engine performance

### Optimum performance

- Suitable for all driving conditions;
- Good thermal stability and good oxidation resistance
- Shear stability ensuring perfect lubrication in both hot and cold conditions

## CHARACTERISTICS

	Method	Units	SAE Grade 10W-40
Density at 15°C	ASTM D1298	Kg/m <sup>3</sup>	866
Viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	102
Viscosity at 100°C	ASTM 445	mm <sup>2</sup> /s	14.7
Viscosity index	ASTM D2270	-	149
Pour point	ASTM D97	°C	-33
Flash point	ASTM D92	°C	234

The typical characteristics mentioned represent mean values

**TOTAL LUBRIFIANTS – Immeuble Spazio**  
562, avenue du Parc de l'île  
92029 Nanterre cedex  
France

### ELF EVOLUTION 500 FT

Last update of this datasheet: 10/2015



This lubricant used in accordance with our recommendations and for the application for which it is intended does not represent a special hazard. A safety data file conforming to the requirements of current EC legislation is available from your local trade consultant.