



A brand of **TOTAL**

ELF EVOLUTION 500 FT 15W-50



Premium multi-grade motor oil using ELF mineral technology, intended for lubricating gasoline passenger car engines

APPLICATIONS

Most recent technology engines

- Premium multi-grade motor oil for all engines, recommended for all high performance gasoline engine cars equipped with direct or indirect injection, multi valve and turbo-charge technologies

In all conditions

- Suitable for all conditions (in town, on highways or motorways); Meets needs of motor manufacturers regarding extended oil change intervals

Refer to the maintenance book of your vehicle to know the recommendation of the

PERFORMANCES

International specifications

API SN

CUSTOMER BENEFITS

Excellent engine protection

- Improved engine cleanliness
- Very high anti-wear and anti-corrosion properties that maintain engine performance

Optimum performance

- Suitable for all driving conditions;
- Good thermal stability and good oxidation resistance
- Shear stability ensuring perfect lubrication in both hot and cold conditions

CHARACTERISTICS

	Method	Units	SAE Grade 15W-50
Density at 15°C	ASTM D1298	Kg/m ³	873
Viscosity at 40°C	ASTM D445	mm ² /s	165
Viscosity at 100°C	ASTM 445	mm ² /s	19
Viscosity index	ASTM D2270	-	152
Pour point	ASTM D97	°C	-30
Flash point	ASTM D92	°C	243

The typical characteristics mentioned represent mean values

TOTAL LUBRIFIANTS – Immeuble Spazio
562, avenue du Parc de l'île
92029 Nanterre cedex
France

ELF EVOLUTION 500 FT 15W-50

Last update of this datasheet: 10/2015



This lubricant used in accordance with our recommendations and for the application for which it is intended does not represent a special hazard. A safety data file conforming to the requirements of current EC legislation is available from your local trade consultant.