



A brand of **TOTAL**

# ELF EVOLUTION 700 FT 15W-50



*Premium multi-grade motor oil using ELF mineral technology, intended for lubricating gasoline passenger car engines*

## APPLICATIONS

### Most recent technology engines

- Highest specification semi synthetic lubricant recommended for all high performance gasoline engine cars equipped with direct or indirect injection, multi valve and turbo-charge technologies

### In all conditions

- Suitable for all conditions (in town, on highways or motorways); Meets needs of motor manufacturers regarding extended oil change intervals

Refer to the maintenance book of your vehicle to know the recommendation of the

## PERFORMANCES

### International specifications

API SN

## CUSTOMER BENEFITS

### Excellent engine protection

- Outstanding protection against wear

### Optimal performance

- Advanced viscometrics for maximum power and minimum viscous drag
- Prevents sludge build-up and controls oxidation; Optimum power and performance under most severe driving conditions

## CHARACTERISTICS

	Method	Units	SAE Grade 15W-50
Density at 15°C	ASTM D1298	Kg/m3	861
Viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	156
Viscosity at 100°C	ASTM 445	mm <sup>2</sup> /s	20
Viscosity index	ASTM D2270	-	148
Pour point	ASTM D97	°C	-27
Flash point	ASTM D92	°C	249

The typical characteristics mentioned represent mean values

**TOTAL LUBRIFIANTS – Immeuble Spazio**  
562, avenue du Parc de l'île  
92029 Nanterre cedex  
France

**ELF EVOLUTION 700 FT 15W-50**

Last update of this datasheet: 10/2015



This lubricant used in accordance with our recommendations and for the application for which it is intended does not represent a special hazard. A safety data file conforming to the requirements of current EC legislation is available from your local trade consultant.