



A brand of **TOTAL**

# ELF EVOLUTION 700 FT 5W-40



*Premium multi-grade motor oil using ELF mineral technology, intended for lubricating gasoline passenger car engines*

## APPLICATIONS

### Most recent technology engines

- Highest specification semi synthetic lubricant recommended for all high performance gasoline engine cars equipped with direct or indirect injection, multi valve and turbo-charge technologies

### In all conditions

- Suitable for all conditions (in town, on highways or motorways); Meets needs of motor manufacturers regarding extended oil change intervals

Refer to the maintenance book of your vehicle to know the recommendation of the

## PERFORMANCES

### International specifications

API SN

## CUSTOMER BENEFITS

### Excellent engine protection

- Outstanding protection against wear

### Optimal performance

- Advanced viscometrics for maximum power and minimum viscous drag
- Prevents sludge build-up and controls oxidation; Optimum power and performance under most severe driving conditions

## CHARACTERISTICS

	Method	Units	SAE Grade 5W-40
Density at 15°C	ASTM D1298	Kg/m <sup>3</sup>	857
Viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	91
Viscosity at 100°C	ASTM 445	mm <sup>2</sup> /s	14.6
Viscosity index	ASTM D2270	-	168
Pour point	ASTM D97	°C	-39
Flash point	ASTM D92	°C	226

The typical characteristics mentioned represent mean values

TOTAL LUBRIFIANTS – Immeuble Spazio  
562, avenue du Parc de l'île  
92029 Nanterre cedex  
France

### ELF EVOLUTION 700 FT 5W-40

Last update of this datasheet: 10/2015



This lubricant used in accordance with our recommendations and for the application for which it is intended does not represent a special hazard. A safety data file conforming to the requirements of current EC legislation is available from your local trade consultant.