



A brand of **TOTAL**

ELF EVOLUTION 700 FTX 5W-30



Premium multi-grade motor oil using ELF mineral technology, intended for lubricating gasoline passenger car engines



APPLICATIONS

Most recent technology engines

- High specification semi synthetic lubricant recommended for all high performance gasoline engine cars equipped with direct or indirect injection, multi valve and turbo-charge technologies

In all conditions

- Suitable for all conditions (in town, on highways or motorways); Meets needs of motor manufacturers regarding extended oil change intervals

Refer to the maintenance book of your vehicle to know the recommendation of the

PERFORMANCES

International specifications

API SN ; ILSAC GF-5

CUSTOMER BENEFITS

Fuel Economy

- Promoted fuel saving

Excellent engine protection

- Outstanding protection against wear

Optimal performance

- Advanced viscometrics for good power and minimum viscous drag
- Prevents sludge build-up and controls oxidation; Optimum power and performance under most severe driving conditions

	Method	Units	SAE Grade 5W-30
Density at 15°C	ASTM D1298	Kg/m3	858
Viscosity at 40°C	ASTM D445	mm ² /s	61
Viscosity at 100°C	ASTM 445	mm ² /s	10.2
Viscosity index	ASTM D2270	-	155
Pour point	ASTM D97	°C	-36
Flash point	ASTM D92	°C	230

The typical characteristics mentioned represent mean values

TOTAL LUBRIFIANTS – Immeuble Spazio
562, avenue du Parc de l'île
92029 Nanterre cedex
France

ELF EVOLUTION 700 FTX 5W-30

Last update of this datasheet: 02/2018



This lubricant used in accordance with our recommendations and for the application for which it is intended does not represent a special hazard. A safety data file conforming to the requirements of current EC legislation is available from your local trade consultant.