



A brand of **TOTAL**

# ELF EVOLUTION 900 FT 5W-50



*Top performance motor oil using ELF fully synthetic technology, intended for lubricating gasoline passenger car engines*

## APPLICATIONS

### Most recent technology engines

- Recommended for all high performance gasoline engine cars equipped with direct or indirect injection, multi-valve and turbo-charge technologies
- Suitable for protection under severe driving style or conditions

### Even in very severe conditions

- Stability and endurance under severe conditions(heat, load, speed)that can cause conventional oils to break down

Refer to the maintenance book of your vehicle to know the recommendation of the

## PERFORMANCES

### International specifications

API SN

## CUSTOMER BENEFITS

### Excellent engine protection

- Protects moving parts even at very high operating temperatures

### Optimal performance

- Extended oil change intervals; Thermal resistance and reliability gain; Excellent start-up performance and prevents sludge build-up and controls oxidation
- Keeps engine clean for consistent engine power output

## CHARACTERISTICS

	Method	Units	SAE Grade 5W-50
Density at 15°C	ASTM D1298	Kg/m <sup>3</sup>	854
Viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	129
Viscosity at 100°C	ASTM 445	mm <sup>2</sup> /s	19.5
Viscosity index	ASTM D2270	-	173
Pour point	ASTM D97	°C	-36
Flash point	ASTM D92	°C	249

The typical characteristics mentioned represent mean values

**TOTAL LUBRIFIANTS – Immeuble Spazio**  
562, avenue du Parc de l'île  
92029 Nanterre cedex  
France

**ELF EVOLUTION 900 FT 5W-50**

Last update of this datasheet: 10/2015



This lubricant used in accordance with our recommendations and for the application for which it is intended does not represent a special hazard. A safety data file conforming to the requirements of current EC legislation is available from your local trade consultant.