



ELF MOTO 4 PRO TECH 5W-40

4-stroke motor oil

KEY DATA

- MOTORCYCLE RANGE



- INTERNATIONAL STANDARDS

- ✓ API SL
- ✓ JASO MA2

- 4-STROKE MOTOR OIL
- SYNTHETIC TECHNOLOGY
- SAE 5W40



APPLICATIONS

ELF MOTO 4 PRO TECH 5W-40 is particularly recommended for all mechanically demanding 4-stroke motorcycle engines.

ELF MOTO 4 PRO TECH 5W-40 is suitable for all urban traffic usage, country drives and high speed motorway journeys.

ELF MOTO 4 PRO TECH 5W-40 formula protects catalytic converters thanks to the use of specific additives. The oil-change intervals recommended by the manufacturers and the minimum required viscosities must be complied with. This lubricant is compatible with leadfree fuels.

CUSTOMER BENEFITS

- ELF MOTO 4 PRO TECH 5W-40** has successfully undergone a very harsh oxidation test. This high quality lubricant has good thermal stability, it remains fluid and efficient through all variations in temperature.
- The additives and base oils used in the **ELF MOTO 4 PRO TECH 5W-40** formula act against the formation of deposits, and maintain hydrodynamic lubrication at high engine speeds. **ELF MOTO 4 PRO TECH 5W-40** provides an immediate response to engine demands: harsh acceleration, flat-out power.
- HTHS viscosity (High Temperature High Shear) of **ELF MOTO 4 PRO TECH 5W-40** provides users with ideal performance under extreme pressure conditions. The viscosity chosen ensures engine protection thanks to its anti-wear property (oil film thickness). The molecular structure of the lubricant withstands extreme transmission pressures.
- Special additives set up a protective coating which improves gear shift comfort, reduces transmission mechanical noise and protects metal components in contact. The base oils form an even film of oil between the clutch discs in order to prevent clutch disc slip and wear.



CHARACTERISTICS*

Test	Unit	Result
Viscosity grade	-	5W-40
Density at 15°C	kg/m ³	853
Kinematic viscosity at 40°C	mm ² /s	85
Kinematic viscosity at 100°C	mm ² /s	14
Viscosity index	-	
Pour Point	°C	-39
OC Flash Point	°C	228

*The characteristics given above are obtained with a standard tolerance threshold during production and may not be considered specifications.

RECOMMENDATIONS FOR USE

Before using the product, the vehicle's user guide should be checked. Oil changes should be carried out in accordance with the manufacturer's recommendations.

The product should not be stored at temperatures over 60°C. It should be kept away from sunlight, intense cold and extreme temperature fluctuations.

If possible, the packaging should not be exposed to the elements. Otherwise, the drums should be laid horizontally in order to avoid any contamination from water and to prevent the product's label from rubbing off.

HEALTH, SAFETY AND THE ENVIRONMENT

Based on the toxicological information available, this product should not cause any adverse health effects, provided it is used for its intended purpose and in accordance with the recommendations laid out in the Safety Data Sheet. This can be obtained on request from your local reseller and is available for consultation at www.quickfds.com.

This product should not be used for any purposes other than the ones for which it is intended.

When disposing of the product after use, please protect the environment and comply with local regulations.

TOTAL Lubrifiants
Immeuble Le Spazio
562, avenue du Parc de l'île
92029 Nanterre Cedex
France

Last update of this datasheet: 01/2014

ELF MOTO 4 PRO TECH 5W-40



Some variations can be expected under normal production conditions, but these should not affect the product's expected performance irrespective of the site. The information contained in this document is subject to change without notice. Our products can be viewed on our website at www.lubrifiants.total.fr.