



ELF MOTO GEAR OIL 80W90

Extreme pressure lubricant specially developed for 4-stroke motorcycle gearboxes.

USE

Motorcycle application

- MOTO GEAR OIL 80W-90 is particularly recommended for harsh conditions. Its formula is suitable for 4-stroke motorcycle manual gearboxes.

PERFORMANCES

- **Selected mineral compounds**
 - MOTO GEAR OIL 80W-90 is a lubricant using selected mineral compounds.
- **Grade**
 - SAE grade: 80W-90 recommended by the major 4-stroke motorcycle constructors.
- **API GL5**
 - MOTO GEAR OIL 80W-90 meets the most stringent requirements of the international API standard as required by the 4-stroke motorcycle constructors.

CUSTOMER ADVANTAGES

- **Good sprocket resistance**
 - Extreme pressure and anti-wear properties providing good sprocket resistance under high loads and undergoing repeated shock.
- **Resistance**
 - High resistance to alteration, ensuring performance stability.
- **Anti-corrosion**
 - Anti-corrosion properties for steel and copper.
- **All temperatures**
 - Good viscosity index and low pour-point ensuring efficient lubrication at all temperatures.
 - Good thermal stability.
- **Protects gaskets**
 - Neutral for seals.
 - Anti-foaming capacity.

PROPERTIES

<u>PHYSICAL-CHEMICAL PROPERTIES</u>	<u>MOTO GEAR OIL 80W90</u>	
SAE grade	80W-90	
Density at 15 °C	0.9	
Kinematic viscosity at 40 °C	144	mm ² /s (Cst)
Kinematic viscosity at 100 °C	15	mm ² /s (Cst)
Pour point	-27	°C

The specifications in this table are averages given for information only.

TOTAL LUBRIFIANTS
Immeuble Spazio
562, avenue du Parc de l'île
92029 Nanterre cedex
France

ELF MOTO GEAR OIL 80W-90
05/2014



1/1
This multilubricant when used according to our recommendations and for the purpose for which it is intended presents no particular hazard. A safety data sheet complying with current EC legislation can be obtained on www.quick-fds.com and from your local commercial advisor.