



A brand of **TOTAL**

ELF PERFORMANCE SUPER D 40



Mineral lubricant suitable for diesel engines.

APPLICATIONS

- ELF PERFORMANCE SUPER D 40 is a **mineral** lubricant recommended for **old diesel engines of transport, public works materials, agricultural vehicles...**
- It is also suitable for **stationary engines**.
- ELF PERFORMANCE SUPER D 40W is suitable for all diesel engines when an **SAE 40 grade lubricant is recommended**.

APPROVALS

Specifications

API CF/SF

PERFORMANCES AND CUSTOMER BENEFITS

- ELF PERFORMANCE SUPER D 40 exhibits **good resistance to oxidation**, preventing the formation of deposits and varnishes.
- **Detergent, dispersant and anti-wear properties** keep the **engine clean** and enable effective control of soot, sludge and piston deposits.

PHYSICAL AND CHEMICAL CHARACTERISTICS

ELF PERFORMANCE SUPER D 40		Method	Value
Density at 15°C	kg/m ³	ASTM D1298	880
Kinematic Viscosity at 40°C	mm ² /s	ASTM D445	126.2
Kinematic Viscosity at 100°C	mm ² /s	ASTM D445	13.3
Viscosity Index	-	ASTM D2270	99
Flash point	°C	ASTM D92	>220
Pour Point	°C	ASTM D97	-24
T.B.N	mgKOH/g	ASTM D2896	11
Sulphated Ash	% m/m	ASTM D874	1.52

The features mentioned above are average values obtained with some variability in production and do not constitute a specification.