



A brand of **TOTAL**

# EVOLUTION 400 15W-40



Premium mineral oils designed for petrol and diesel engine oil.  
Suitable for use under standard conditions.

## APPLICATIONS

**Old gasoline and diesel car engines**

• These oils can be used with petrol or diesel engine technologies without particulate filters and engines built prior to 2001 and designed for use with mineral oils in these viscosities.

**In all conditions**

• Suitable for all conditions (in town, on highways or motorways); Meets needs of motor manufacturers regarding extended oil change intervals

Refer to the maintenance book of your vehicle to know the recommendation of the

## PERFORMANCES

**International specifications**

API SL/CF

## CUSTOMER BENEFITS

- Protection and reliability
- Protects engines against deposits.
- Oil film able to withstand high operating temperatures
- Standard drain interval.

## CHARACTERISTICS

	Method	Units	SAE Grade 15W-40
Density at 15°C	ASTM D1298	Kg/m <sup>3</sup>	868,3
Viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	90,5
Viscosity at 100°C	ASTM 445	mm <sup>2</sup> /s	13,6
Viscosity index	ASTM D2270	-	152
Pour point	ASTM D97	°C	-33
Flash point	ASTM D92	°C	> 230

The typical characteristics mentioned represent mean values

**TOTAL LUBRIFIANTS – Immeuble Spazio**  
562, avenue du Parc de l'île  
92029 Nanterre cedex  
France

**ELF EVOLUTION 400 15W-40**

Last update of this datasheet: 08/2017



This lubricant used in accordance with our recommendations and for the application for which it is intended does not represent a special hazard.  
A safety data file conforming to the requirements of current EC legislation is available from your local trade consultant.