



A brand of **TOTAL**

# EVOLUTION 500 DIESEL 15W-40



*Multigrade oil specially designed for Diesel engines in cars.*

## APPLICATIONS

### Diesel engines

- Recommended for all Diesel engines in cars, MPVs and vans.
- The right lubricant for all types of service (urban use, on the highway or long motorway journeys) and for long-term use at all times of year.

Refer to the maintenance book of your vehicle to know the recommendation of the manufacturer

## PERFORMANCES

### International specifications

ACEA : A3/B3  
API : SL/CF

### OEMs approvals

RENAULT Diesel (vehicles before october 2007)  
VOLKSWAGEN VW 505.00

## CUSTOMER BENEFITS

### Mineral technology oil dedicated to Diesel engines

- Specially developed for Diesel engines. Guarantees perfect engine lubrication.

## CHARACTERISTICS

	Method	Units	SAE Grade 15W-40
Density at 15°C	ASTM D1298	kg/m <sup>3</sup>	884
Viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	103,2
Viscosity at 100°C	ASTM 445	mm <sup>2</sup> /s	13,8
Viscosity index	ASTM D2270	-	136
Pour point	ASTM D97	°C	- 27
Flash point	ASTM D92	°C	230

The typical characteristics mentioned represent mean values