



A brand of TOTAL

EVOLUTION 900 USX 5W-30



High performance lubricant using ELF synthetic technology, intended for lubricating all Gasoline car engines.



APPLICATIONS

All Gasoline engines, particularly those of recent technology

- Recommended for all recent gasoline engines, multivalve and turbocharged, direct injection including downsized engine and those with post-treatment system
- Particularly adapted to recent GENERAL MOTORS, FORD vehicles

The most severe journeys

- Suitable for all journeys (in town, on highways, or motorways) and particularly in severe conditions

« Vigorous » driving, all times of year

- For all driving styles, particularly « vigorous » and high speeds.

Refer to the maintenance book of your vehicle to know the recommendation of the manufacturer

PERFORMANCES

International specifications

API SN PLUS
ILSAC GF-5

OEM Specifications

CHRYSLER MS-6395
GENERAL MOTORS Dexos 1™ Gen2
FORD FORD M2C 946-A

CUSTOMER BENEFITS

A better environment protection

- Significant FUEL ECONOMY performances measured by the official ILSAC test: sequence VI D.

Extended oil change intervals

- Meets the most demanding OEM requirements enabling very extended oil change intervals, thanks to an outstanding oxidation resistance.

Excellent engine protection and cleanliness

- New formulation adapted to control the risk of LSPI (Low Speed Pre-Ignition) of the "Downsized" engines. This lubricant gives the engine an excellent wear protection, thanks to its very solid additive package.
- Ensures maximum engine cleanliness, thanks to very good detergent and dispersion properties.

CHARACTERISTICS

	Method	Units	SAE Grade 5W-30
Density at 15°C	ASTM D1298	kg/m ³	852
Viscosity at 40°C	ASTM D445	mm ² /s	62,2
Viscosity at 100°C	ASTM 445	mm ² /s	10,4
Viscosity index	ASTM D2270	-	184
Pour point	ASTM D97	°C	-45
Flash point	ASTM D92	°C	>220

The typical characteristics mentioned represent mean values