



A brand of **TOTAL**

SPORTI TXI 5W-40



Lubricant using ELF synthetics technology, intended for all Gasoline and Diesel car engines.

APPLICATIONS

**All Gasoline/Diesel engines
Direct injection Diesel**

• Recommended for all Gasoline engines (multivalve, turbocharged, with or without catalytic converter) and all Diesel engines – with or without turbocharging – in cars and light vans.

**The most severe journeys
All times of year**

• Suitable for all journeys (in town, on highways and motorways) and particularly in severe conditions.

“Vigorous” driving

• For all driving styles, particularly “vigorous” and high speeds.

Refer to the maintenance book of your vehicle to know the recommendation of the manufacturer

PERFORMANCES

International specifications

ACEA : A3/B4
API : SL/CF

CUSTOMER BENEFITS

High performance

• Excellent engine protection, particularly against timing system wear.

Lengthens engine life

• Immediate lubrication of engine parts during cold starts, leading to longer engine life.

Extended oil change intervals

• ELF Sporti TXI 5W-40 meets the requirements of the manufacturers as regards extended oil change intervals.

CHARACTERISTICS

	Method	Units	SAE Grade 5W-40
Density at 15°C	ASTM D1298	kg/m ³	854
Viscosity at 40°C	ASTM D445	mm ² /s	87
Viscosity at 100°C	ASTM 445	mm ² /s	14,3
Pour point	ASTM D97	°C	- 36
Flash point	ASTM D92	°C	220
B.N.	ASTM D2896	mgKOH/g	10

The typical characteristics mentioned represent mean values