



A brand of **TOTAL**

## TRANSELF LD 75W-80



**Extreme pressure semi-synthetic lubricant for mechanical gearboxes.**



### APPLICATIONS

- Fuel Economy oil recommended for all mechanical transmissions in trucks and light vans working in the most severe conditions
- TRANSELF LD 75W-80 is highly suitable for EATON gearboxes for which the oil drain interval can reach 300 000 km

### APPROVALS

|                                |  |
|--------------------------------|--|
| <b>Specifications</b>          | API GL-4   |
| <b>Manufacturers' approval</b> | MAN 341 Type E3 & Z4<br>Volvo 97307<br>ZF TE-ML 01L, 02L, 16K<br>Suitable for EATON Europe Manual Transmission |

### PERFORMANCES AND CUSTOMER BENEFITS

#### Highly effective

#### Advance protection for transmission systems

#### Very extended drain interval

#### Fuel savings

- High viscosity index..
- Good Extreme-Pressure and anti-wear properties.
- Very high antifoam, anticorrosion and antirust properties.
- Very good oxidation stability.
- Very low viscosity drop through shear.
- Driving comfort.
- Excellent stability in service.
- Compatible with most types of synchronisers.
- Very extended drain interval
- Easy start at cold temperatures
- Fuel savings

### PHYSICAL AND CHEMICAL CHARACTERISTICS

| TRANSELF LD 75W-80           |                    | Method     | Value |
|------------------------------|--------------------|------------|-------|
| Density at 15°C              | --                 | ASTM D1298 | 883   |
| Kinematic Viscosity at 40°C  | mm <sup>2</sup> /s | ASTM D445  | 64    |
| Kinematic Viscosity at 100°C | mm <sup>2</sup> /s | ASTM D445  | 9.5   |
| Viscosity Index              | -                  | ASTM D2270 | 124   |
| Pour Point                   | °C                 | ASTM D97   | -41   |

*The features mentioned above are average values obtained with some variability in production and do not constitute a specification.*